



NOTES:

- $\triangle 1$ USE 7 GAUGE REINFORCEMENT FOR HOLLOW METAL FRAMES.
- $\triangle 2$ USE 12 GAUGE REINFORCEMENT FOR HOLLOW METAL DOORS.
- $\triangle 3$ MINIMUM OPENING REQUIRED FOR CLOSER BODY.
- $\triangle 4$ A REMOVABLE STOP IS REQUIRED FOR DOOR WIDTHS UNDER 2" THICK, SEE TEMPLATE A7783 FOR REMOVABLE STOP FRAME DETAIL.
- $\triangle 5$ MAXIMUM DEGREE OF OPENING 100°.
- $\triangle 6$ LEFT HAND DOOR AND CLOSER SHOWN, RIGHT HAND OPPOSITE.
- $\triangle 7$ 15" X 2" CUT OUT REQUIRED FOR DOOR CLOSER MOUNTING PLATE & COVER PLATE

SARGENT® Manufacturing Company
 100 Sargent Drive New Haven, CT 06511

DATA SHEET:
 268 CSP, CSPS OR CSPD OVERHEAD
 CONCEALED SECURITY CLOSER
 WITH OFFSET PIVOT

RELEASE DATE

3 Mar 08

TEMPLATE NO.
 A7784 B