



LEFT HAND REVERSE BEVEL SHOWN
RHRB SIMILAR BUT OPPOSITE

NOTES:

1. MOUNTING HOLES TO BE PREPARED AT INSTALLATION.
2. SURFACE OF DOOR WHERE EXIT DEVICE IS TO BE APPLIED MUST BE FLUSH. NO INSIDE PANELS, LITE KITS OR SHIMS PERMITTED BETWEEN DEVICE AND DOOR SKIN
3. SEE STRIKE TEMPLATE NUMBER 4449 (STANDARD) FOR TOP STRIKE.
4. TOLERANCE ON ALL DIMENSIONS ± 1/64"
5. SEE TEMPLATES 4569 AND 4571 FOR ELECTRICAL RACEWAY DATA
6. MORTISE LOCK IS CENTERED AT 7/8" FROM INSIDE SKIN FOR ALL DOOR THICKNESSES
7. SEE TEMPLATE 4617 FOR THERMAL PIN PREP (REQUIRED FOR FIRE RATED APPLICATIONS OVER 20 MINUTES)

SARGENT Manufacturing Company
100 Sargent Drive New Haven, CT 06511

TEMPLATE: CENTER AND TOP LATCH CONCEALED
VERTICAL ROD EXIT DEVICE FOR WOOD DOORS
SINGLE DOOR APPLICATIONS SP-8600 AND 12-SP-8600

RELEASE DATE
JUNE 8, 2009
TEMPLATE NO.
4648 A