



















# Windstorm Products Single Doors

Max. Design Pressure:	+/-57.2 psf	+/-72 psf	+/-80 psf	+/-85 psf	+/-85 psf	+/-100 psf
Max. Opening Size:	4'0" x 7'0"	3'0" x 7'0"	3'0" x 7'0"	3'0" x 7'0"	3'0" x 7'0"	3'0" x 7'0"
Max. Door Size:	4'0" x 7'0"	3'0" x 7'0"	3'0" x 7'0"	3'0" x 7'0"	3'0" x 7'0"	3'0" x 7'0"
Face Type:	Flush (F)	Any glazed unit for 12" to 24" wide (HG)	Flush (F)	Flush (F)	Flush (F)	Flush (F)
Report Number:	ATI 16779	TS J99021846-231-0	ATI 02.30114	ATI 15813-N	ATI 16778	ATI 02.30013
Dade Acceptance No.	02-0814.05	00-0307.09	02-0222.07	01-1102.02	02-0814.05	02.0222.07
Expiration Date:	09/19/2007	N/A	03/25/2007	01/31/2007	09/19/2007	03/25/2007

<b>CURRIES®</b>						
Door:	747	707	707	707	747	707
Date of Test:	12/16/95	08/10/03	09/19/97	07/21/95	12/13/95	08/12/97
Astragal:	N/A	N/A	N/A	N/A	N/A	N/A
Vision Lite Kit Type:	N/A	Type 1 Only	N/A	N/A	N/A	N/A
Anchors:	Masonry T	Masonry T	Masonry T	Masonry T	Masonry T	Masonry T
	WPS	WPS	WPS	WPS	WPS	WPS

<b>McKINNEY®</b>						
Hinge:	TA2714	TA2714	TA2714	TA2714	TA2714	TA2714

<b>SARGENT®</b>						
Hardware:	HC8800	8200*, 10 Line	8900	6500	8200*	8200*

**Test Notes:**

1. All CURRIES doors tested with SARGENT locking hardware and McKINNEY hinges and appropriate auxiliary hardware.
2. Glazed door may be glazed with any Dade County approved 1/4" thick clear polycarbonate.
3. Sizes shown maximum allowed. Smaller sizes may be used.

Contact CURRIES for detailed frame/door requirements and limitations, as well as all auxiliary hardware requirements.

\*Deadbolt function not required for NOA/Certification, but may be used.

Please refer to the Notice of Acceptance (NOA) to determine all restrictions and associated hardware required.